# U.S.S.N. 10/658,708

### Listing of the Claims

- 1. (Original) An apparatus for dispensing a liquid onto a substrate, comprising:
  - a support for receiving the substrate;
- a dispensing head for dispensing the liquid onto the substrate;
- a knife ring vertically adjustably mounted beneath said support; and
- a vertical adjustment mechanism operably engaging said knife ring for placing said knife ring at selected vertical positions beneath the substrate.
- 2. (Original) The apparatus of claim 1 wherein said vertical adjustment mechanism comprises at least one fluid-actuated ring actuating cylinder.
- 3. (Original) The apparatus of claim 1 wherein said knife ring has a width of about 290 mm.
- 4. (Original) The apparatus of claim 3 wherein said vertical adjustment mechanism comprises at least one fluid-actuated ring actuating cylinder.

## U.S.S.N. 10/658,708

- 5. (Original) The apparatus of claim 2 wherein said at least one fluid-actuated ring actuating cylinder comprises a plurality of fluid-actuated ring actuating cylinders.
- 6. (Original) The apparatus of claim 5 wherein said knife ring has a width of about 290 mm.
- 7. (Original) The apparatus of claim 2 wherein said at least one fluid-actuated ring actuating cylinder is actuated by pneumatic pressure.
- 8. (Original) The apparatus of claim 7 wherein said knife ring has a width of about 290 mm.
- 9. (Original) The apparatus of claim 7 wherein said at least one fluid-actuated ring actuating cylinder comprises a plurality of fluid-actuated ring actuating cylinders.
- 10 (Original). The apparatus of claim 9 wherein said knife ring has a width of about 290 mm.

### U.S.S.N. 10/658,708

- 11. (Original) An apparatus for dispensing a liquid onto a substrate, comprising:
  - a support for receiving the substrate;
- a dispensing head for dispensing the liquid onto the substrate;
- a knife ring vertically adjustably mounted beneath said support; and
- at least one hydraulic-powered ring actuating cylinder operably engaging said knife ring for placing said knife ring at selected vertical positions beneath the substrate.
- 12. (Original) The apparatus of claim 11 wherein said knife ring has a width of about 290 mm.
- 13. (Original) The apparatus of claim 11 wherein said at least one ring actuating cylinder comprises a plurality of ring actuating cylinders.
- 14. (Original) The apparatus of claim 13 wherein said knife ring has a width of about 290 mm.

#### 15. - 20. (Cancelled)